
Assembly & Installation Instructions



PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

IMPORTANT:

1. WARNING - Disconnect power before relamping or wiring the fixture.
Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

INSTALLATION STEPS:

1. Select the suspension rods of your desired height. Thread the fixture's wires through the rods and canopy, then tighten to secure both the rods and canopy to the light fixture.
2. Secure the mounting plate to the junction box using the mounting screws.
3. Connect the wires using the wire caps as follows:
   Connect the fixture's **BLACK** wire to the home **LIVE/HOT** wire.
   Connect the fixture's **WHITE** wire to the home **NEUTRAL** wire.
   Connect the fixture's GREEN wire to the home **GROUND** wire to the mounting plate with the green screw.
   Note: Ensure no wire strands are exposed.
4. Secure the canopy to the mounting plate using the knob caps.
5. Install the bulb into the lamp holder.
6. Secure the acrylic sheet inside the fabric shade.
7. Restore the power to check if the light works properly.