
Assembly & Installation Instructions



PREPARATION before INSTALLATION:

1. If an existing fixture is being replaced, remove it and note to which wire in the outlet box the original fixture was attached.
2. Before discarding the carton, double-check the packaging to make sure all parts have been found.
3. This fixture was designed to be mounted on an octagon outlet box. The box must be securely mounted to the structure of the building.

IMPORTANT:

1. WARNING - Disconnect power before relamping or wiring the fixture.
Turn off the entire electrical circuit to which the lighting fixture is attached.
2. Installation and maintenance of this fixture should be completed by a licensed electrician.
3. Failure to install the fixture correctly could result in serious injury or death.
4. Read all instructions before starting installation.

INSTALLATION STEPS:

Step 1:Open Arms Evenly
Spread the lamp arms evenly into three equal sections.
Step 2:Attach Downrod
Pass the main and ground wires through the downrod, then tighten and secure the downrod onto the lamp body. (Rod length can be extended by connecting additional rods)
Step 3:Install Ceiling Canopy
Pass the main and ground wires through the ceiling canopy, then secure the canopy onto the downrod.
Step 4:Mount Bracket
Secure the mounting bracket to the U.S. standard junction box using screws.
Step 5:Connect Wires
Connect the fixture wires to the pre-installed wires in the junction box using wire connectors:
-Black to Live (Hot), White to Neutral, and Ground to Ground via the green grounding screw on the mounting bracket.
-Ensure no wires are exposed during the wiring .
Steps 6-7:Attach Ceiling Canopy
Cover the mounting bracket with the ceiling canopy and secure it using the decorative nuts.
Step 8:Install Bulb
Install the bulb (bulb not included).
Step 9:Attach Lampshade
Install the lampshade to the socket (align the threads properly and avoid excessive force).